

Item		Parameters
Print parameters	Printing Method	Thermal Line
	Printing width	72mm
	Resolution	576 Dots/Line or 512 Dots/Line(8dots/mm,203dpi)
	Print speed	300mm/Second
	Interface	LAN (100M)+USB+COM: LAN(100M)+USB+WIFI:USB+GPRS:USB+COM:USB+ Bluetooth
	Line Spacing	3.75mm(Can adjust line spacing by command)
	Line No.	FontA-48Lines/FontB-64Lines/Simple, traditional Chinese-24 lines
	Character	standard GB18030 simplified / traditional Chinese Fonts
	Character Size	ANK character, Font A:1.5×3.0mm(12×24 dots) Font B:1.1×2.1mm(9×17 dots) Simplified/Traditional Chinese:3.0×3.0mm(24×24 dots)
Bar code Character	Extended character set	PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/Greek/Hebrew/ EastEurope/Iran/WPC1252/PC866/PC852/PC858/IranII/Latvian/Arabic/ PT151,1251/PC737/WPC/1257/ThaiVietnam/PC864/PC1001/(Latvian)/ (PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)
	Bar code	1D bar code:UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/CODABAR/CODE93/CODE128 2D barcode: QRCODE
Graphics printing	Graphics printing	Supports bitmap download and print
Cutter	Cutter Function	Full cut/Half cut
Paper	Type	Thermal
	Width	79.5±0.5mm
	Diameter	≤80mm
	Feed method	Easy feed (Clame shell feed)
Print commands	Commands	ESC/POS
Power	Power Adaptor	Input: AC 100V-240V,50~60Hz Output: DC 24V/2.5A
	Cash Drawer output	DC 24V/1A
Buffer	Input Buffer	2048K bytes
	NV Flash	256K bytes
physical characteristics	Weight	1.2KG
	Dimension	186*145*135
environment	Working	Temp:5 ~ 45 degree, Humidity:10 ~ 80%
	Storage	Temp:-10 ~ 50 degree ,Humidity:10 ~ 90%(No dew)
Reliability parameter	Print Head Life	100KM(print density≤12.5)
	Cutter Life	1000,000times
Software	Driver	Android,IOS,Linux,Win2000,Win2003,WinXP,Win7,Win8,Win8.1